

Dimensiones y Pesos Tubería acero con y sin costura convencionales de acuerdo a fórmula peso específico 7850 kg/m<sup>3</sup>

Nominal Diameter	Diametro Exterior		Espesor de Pared		Cédula Schedule / Designation	Weight Lb/ft	Peso Kg/m
	Outside Diameter	mm	in	mm			
1/8	0.405	10.3	0.035	0.89	5	0.14	0.21
			0.049	1.24	10	0.19	0.28
			0.068	1.73	40 STD	0.24	0.36
			0.095	2.41	80 XS	0.31	0.47
1/4	0.540	13.7	0.049	1.24	5	0.26	0.38
			0.065	1.65	10	0.33	0.49
			0.088	2.24	40 STD	0.43	0.63
			0.119	3.02	80 XS	0.54	0.80
3/8	0.675	17.1	0.049	1.24	5	0.33	0.49
			0.065	1.65	10	0.42	0.63
			0.091	2.31	40 STD	0.57	0.85
			0.126	3.20	80 XS	0.74	1.10
1/2	0.840	21.3	0.065	1.65	5 5S	0.54	0.80
			0.083	2.11	10 10S	0.67	1.00
			0.109	2.77	40 STD	0.85	1.27
			0.147	3.73	80 XS	1.09	1.62
3/4	1.050	26.7	0.188	4.78	160	1.31	1.95
			0.294	7.47	XXS	1.72	2.55
			0.065	1.65	5 5S	0.68	1.02
			0.083	2.11	10 10S	0.86	1.28
1	1.315	33.4	0.113	2.87	40 STD	1.13	1.68
			0.154	3.91	80 XS	1.48	2.20
			0.219	5.56	160	1.95	2.90
			0.308	7.82	XXS	2.44	3.64
1 1/4	1.660	42.2	0.065	1.65	5 5S	0.87	1.29
			0.109	2.77	10 10S	1.41	2.09
			0.140	3.56	40 STD	2.27	3.39
			0.191	4.85	80 XS	3.00	4.46
1 1/2	1.900	48.3	0.250	6.35	160	3.77	5.61
			0.382	9.70	XXS	5.22	7.77
			0.065	1.65	5 5S	1.28	1.90
			0.109	2.77	10 10S	2.09	3.11
2	2.375	60.3	0.145	3.68	40 STD	2.72	4.05
			0.200	5.08	80 XS	3.63	5.41
			0.281	7.14	160	4.86	7.24
			0.400	10.16	XXS	6.41	9.55
2 1/2	2.875	73.0	0.065	1.65	5 5S	1.61	2.39
			0.109	2.77	10 10S	2.64	3.93
			0.154	3.91	40 STD	3.66	5.44
			0.172	4.37		4.05	6.03
3	3.500	88.9	0.188	4.78		4.40	6.54
			0.218	5.54	80 XS	5.03	7.48
			0.250	6.35		5.68	8.45
			0.281	7.14		6.29	9.36
3 1/2	4.250	108.3	0.344	8.74	160	7.47	11.12
			0.436	11.07	XXS	9.04	13.45
			0.083	2.11	5 5S	2.48	3.69
			0.120	3.05	10 10S	3.53	5.26
4	5.000	127.0	0.203	5.16	40 STD	5.80	8.63
			0.216	5.49		6.14	9.14
			0.250	6.35		7.02	10.44
			0.276	7.01	80 XS	7.67	11.41
4 1/2	5.750	146.3	0.375	9.53	160	10.02	14.92
			0.552	14.02	XXS	13.71	20.40
			0.083	2.11	5 5S	3.03	4.51
			0.120	3.05	10 10S	4.34	6.45
5	6.500	165.3	0.125	3.18		4.51	6.71
			0.156	3.96		5.58	8.30
			0.188	4.78		6.66	9.91
			0.216	5.49	40 STD	7.58	11.29
5 1/2	7.250	184.3	0.250	6.35		8.69	12.93
			0.281	7.14		9.67	14.39
			0.300	7.62	80 XS	10.26	15.27
			0.438	11.13	160	14.34	21.34
6	8.000	203.3	0.600	15.24	XXS	18.60	27.68

Dimensiones y Pesos Tubería acero con y sin costura convencionales de acuerdo a fórmula peso específico 7850 kg/m<sup>3</sup>

Nominal Diameter	Diametro Exterior		Espesor de Pared		Cédula Schedule / Designation	Weight Lb/ft	Peso Kg/m
	Outside Diameter	mm	in	mm			
3 1/2	4.000	101.6	0.083	2.11	5 5S	3.48	5.17
			0.120	3.05	10 10S	4.98	7.41
			0.125	3.18		5.18	7.71
			0.156	3.96		6.41	9.54
4	4.500	114.3	0.188	4.78		7.66	11.40
			0.226	5.74	40 STD	9.12	13.57
			0.250	6.35		10.02	14.92
			0.281	7.14		11.17	16.63
4 1/2	5.000	127.0	0.318	8.08	80 XS	12.52	18.63
			0.636	16.15	XXS	22.87	34.04
			0.083	2.11	5 5S	3.92	5.83
			0.120	3.05	10 10S	5.62	8.36
5	5.563	141.3	0.125	3.18		5.85	8.70
			0.156	3.96		7.24	10.78
			0.188	4.78		8.67	12.90
			0.219	5.56		10.02	14.92
6	6.625	168.3	0.237	6.02	40 STD	10.80	16.07
			0.250	6.35		11.36	16.90
			0.281	7.14	60	12.67	18.86
			0.312	7.92		13.97	20.79
7	7.625	193.7	0.337	8.56	80 XS	15.00	22.32
			0.438	11.13	120	19.02	28.31
			0.531	13.49	160	22.53	33.53
			0.674	17.12	XXS	27.57	41.03
8	8.625	219.1	0.247	6.27	40 STD	12.55	18.68
			0.355	9.02	80 XS	17.63	26.23
			0.710	18.03	XXS	32.56	48.46
			0.109	2.77	5 5S	6.36	9.46
9	9.625	244.5	0.125	3.18		7.27	10.81
			0.134	3.40	10 10S	7.78	11.57
			0.156	3.96		9.02	13.42
			0.188	4.78		10.80	16.08
10	10.625	270.0	0.219	5.56		12.51	18.62
			0.258	6.55	40 STD	14.63	21.78
			0.281	7.14		15.87	23.61
			0.312	7.92		17.51	26.06
11	11.625	295.5	0.344	8.74		19.19	28.56
			0.375	9.53	80 XS	20.80	30.95
			0.500	12.70	120	27.06	40.28
			0.625	15.88	160	32.99	49.10
12	12.625	321.0	0.750	19.05	XXS	38.59	57.43
			0.109	2.77	5 5S	7.59	11.30
			0.120	3.05		8.35	12.42
			0.125	3.18		8.69	12.93
13	13.625	346.5	0.134	3.40	10 10S	9.30	13.84
			0.141	3.58		9.77	14.55
			0.149	3.78		10.32	15.35
			0.156	3.96		10.79	16.06
14	14.625	372.0	0.172	4.37		11.87	17.66
			0.188	4.78		12.94	19.25
			0.203	5.16		13.94	20.74
			0.219	5.56		15.00	22.32
15	15.625	397.5	0.237	6.02		16.19	24.09
			0.250	6.35		17.04	25.36
			0.280	7.11	40 STD	18.99	28.27
			0.312	7.92		21.06	31.34
16	16.625	423.0	0.344	8.74		23.10	34.38
			0.375	9.53		25.06	37.29
			0.432	10.97	80 XS	28.60	42.56
			0.500	12.70		32.74	48.72
17	17.625	448.5	0.562	14.27	120	36.43	54.21
			0.625	15.88		40.09	59.66
			0.719	18.26	160	45.40	67.56
			0.750	19.05		47.11	70.10
18	18.625	474.0	0.864	21.95	XXS	53.21	79.19
			0.875	22.23		53.79	80.05
			0.301	7.65	STD	23.57	35.07
			0.500	12.70	XS	38.09	56.68
19	19.625	500.0	0.875	22.23	XXS	63.14	93.97
			0.105	2.67		9.56	14.23
			0.109	2.77	5 5S	9.92	14.77